



Instalace a celkové rozměry B5

Typ motoru	M	N	P	S	T	D	F	G	SS	AC	KK	L
160M	300	250	350	18,5	5	42	12	37	M16	330	2 x M36	655
160L												685
180M	300	250	350	18,5	5	48	14	42,5	M16	380	2 x M36	728
180L												768
200L	350	300	400	18,5	5	55	16	49	M20	420	2 x M48	760
225S	400	350	450	18,5	5	60	18	53	M20	465	2 x M48	825
2p=4,6,8												
225M	400	350	450	18,5	5	55	16	49	M20	465	2 x M48	820
2p=2												
225M	400	350	450	18,5	5	60	18	53	M20	465	2 x M48	850
2p=4,6,8												
225M	400	350	450	18,5	5	60	18	53	M20	465	2 x M48	850
2p=4,6,8												
250M	500	450	550	18,5	5	60	18	53	M20	520	2 x M64	925
2p=2												
250M	500	450	550	18,5	5	65	18	58	M20	520	2 x M64	925
2p=4,6,8												
280S	500	450	550	18,5	5	65	18	58	M20	570	2 x M64	960
2p=2												
280S	500	450	550	18,5	5	75	20	67,5	M20	570	2 x M64	975
2p=4,6,8												
280M	500	450	550	18,5	5	65	18	58	M20	570	2 x M64	1000
2p=2												
280M	500	450	550	18,5	5	75	20	67,5	M20	570	2 x M64	1015
2p=4,6,8												
315S	600	550	660	24	6	65	18	58	M20	650	2 x M64	1160
2p=2												
315M	600	550	660	24	6	65	18	58	M20	650	2 x M64	1270
2p=2												
315L	600	550	660	24	6	65	18	58	M20	650	2 x M64	1270
2p=2												
315S	600	550	660	24	6	80	22	71	M20	650	2 x M64	1190
2p=4,6,8												
315M	600	550	660	24	6	80	22	71	M20	650	2 x M64	1300
2p=4,6,8												
315L	600	550	660	24	6	80	22	71	M20	650	2 x M64	1300
2p=4,6,8												
355M	740	680	800	24	6	75	20	67,5	M20	735	2 x M72	1500
2p=2												
355L	740	680	800	24	6	75	20	67,5	M20	735	2 x M72	1500
2p=2												
355M	740	680	800	24	6	95	25	86	M24	735	2 x M72	1530
2p=4,6,8												
355L	740	680	800	24	6	95	25	86	M24	735	2 x M72	1630
2p=4,6,8												

Typy ložisek a těsnících kroužků pro motory v litinových skříních

Osová výška	Ložiska				Gufera
	Pro motory: B3, B5, B3/B5		Pro motory: V1		
	Strana řidele	Strana ventilátoru	Strana řidele	Strana ventilátoru	
Y(X)3 160	6309	6309	6309	6309	RB45x62x4,5
Y(X)3 180	6311	6311	6311	6311	RB55x75x5,5
Y(X)3 200	6312	6312	6312	6312	RB60x80x5,5
Y(X)3 225	6313	6313	6313	6313	RB65x85x5,5
Y(X)3 250	6314	6314	6314	7314	RB70x90x5,5
Y(X)3 280 2p=2	6314	6314	6314	7314	RB70x90x5,5
Y(X)3 280 2p=4,6,8	6317	6317	6317	7317	RB85x105x5,5
Y(X)3 315 2p=2	6316	6316	6316	7316	RB80x100x5,5
Y(X)3 315 2p=4,6,8	N319	6319	N319	7319	RB95x115x5,5
Y(X)3 355 2p=2	6319	6319	6319	7319	RB95x115x5,5
Y(X)3 355 2p=4,6,8	N322	6322	N322	7322	RB110x130x5,5