

Coils ASC3 and Cable Assemblies

Standards

- ASC3 Coils and cable assemblies conform to Low Voltage Directive



ASC3

Type	Part No.	Voltage	Power Input	Electr. Connection	Protection
ASC3 230V / 50 (60) Hz	801 077	AC	8 W	without plug see cable assemblies	IP65 with plug / cable assembly
ASC3 120V / 50 (60) Hz	801 078				
ASC3 24V / 50 (60) Hz	801 079				
ASC3 24V DC	801 076	DC	17 W	with plug and cable assembly	IP65
DS2-N15 + ASC3 24VAC	804 620 + 801 079	DC	3 W		

Note: Coils are delivered with retainer kit.
Please order cable assemblies separately.



ASC-N15

Cable Assemblies for ASC Coils

Type	Part No.	Temperature Range	Cable length	Wire diameter	Connector Type
ASC-N15	804 570	-50 .. +80°C for stationary use only	1.5m	3 x 0.75 mm ²	loose wires
ASC-N30	804 571		3.0m		
ASC-N60	804 572		6.0m		



DS2-N15

ASC3 24V

Cable Assembly with 24V DC Chopper Plug

- Enables standard 24V AC Coil to be used for DC applications
- Low power assumption (3W only)
- No MOPD degradation

Type	Part No.	Temperature Range	Cable length	Wire diameter	Connector Type
DS2-N15	804 620	-25 .. +80°C	1.5 m	2 x 0.75 mm ²	loose wires

Other Accessories for Solenoid Valves

Type	Part No.	Description
X 11981-1	027 451	Service tool for 110RB, 240RA, 540RA, 3031
ASC3-K01	801 080	Retainer kit (one cap + two O-rings)
PG9 Plug	801 012	Plug according to EN 175301 with cable gland PG 9
PG11 Plug	801 013	Plug according to EN 175301 with cable gland PG 11